

**FORMS OF SUPPLY**LAUROCRYL<sup>®</sup> B-505: 60% solids in toluene**LAUROCRYL B-505****TYPE AND USE**

Pure acrylic thermoplastic resin. Binder for cement facing substrates, low viscosity primers and penetrating stone varnishes.

Suitable for roadmarking paints.

**PRINCIPAL PROPERTIES**

Fast drying.

Good permanent flexibility.

Excellent insulating properties.

**SOLUBILITY**

Aliphatic solvents ..... insoluble

Aromatic hydrocarbons ..... complete

Esters, ketones ..... complete

Alcohols ..... insoluble

**TECHNICAL CHARACTERISTICS**

Non-volatile content (ELOT EN ISO 3251) ..... 60±1%

Viscosity, 60% in toluene

25°C (ELOT EN ISO 2884) mPa.s ..... 3.000 - 9.000

Acid value (ELOT EN ISO 3682 on n.v.) ..... 7 max

Colour, 50% nv

Gardner colour scale (ELOT EN ISO 4630) ..... 2 max

**OTHER CHARACTERISTICS (informative)**

Flash point ..... approx. 4°C

*The information contained herein is provided in good faith and is to the best of our knowledge accurate. Therefore, the buyer is advised to determine the suitability of this product for the intended use. We retain the right to make any changes according to technological progress or further developments. For safety and additional information please refer to the Material Safety Data Sheet as well as to other informative documents accompanying the product.*

LAUROCRYL B-505 en  
Version 1.0