

**FORMS OF SUPPLY**LAUROCRYL<sup>®</sup> B-516: 60% solids in xylene**LAUROCRYL B-516****TYPE AND USE**

Pure acrylic thermoplastic resin. Suitable for spray paints, metal coatings, as well as for cement facing substrates, low viscosity primers and penetrating stone varnishes.

**PRINCIPAL PROPERTIES**

Fast drying  
 Good permanent flexibility  
 Excellent insulating properties  
 Very good adhesion on metallic substrates

**SOLUBILITY**

Aliphatic solvents ..... insoluble  
 Aromatic hydrocarbons ..... complete  
 Esters, ketones ..... complete  
 Alcohols ..... insoluble

**TECHNICAL CHARACTERISTICS**

Non-volatile content (ELOT EN ISO 3251) ..... 60±2%  
 Viscosity, 60% in toluene  
   25°C (ELOT EN ISO 2884) mPa.s ..... 3.000 - 9.000  
 Acid value (ELOT EN ISO 2114 on n.v.) ..... 7 max  
 Colour, 50% nv  
   Gardner colour scale (ELOT EN ISO 4630) ..... 2 max  
**OTHER CHARACTERISTICS (informative)**  
 Flash point ..... approx. 25°C

*The information contained herein is provided in good faith and is to the best of our knowledge accurate. Therefore, the buyer is advised to determine the suitability of this product for the intended use. We retain the right to make any changes according to technological progress or further developments. For safety and additional information please refer to the Material Safety Data Sheet as well as to other informative documents accompanying the product.*

LAUROCRYL B-516 en  
 Version 1.0